



DOSATRON®

■ ■ ■ ■ ■ Because life is powered by water®



WATER TREATMENT

D30 WATER LINE The High-flow Solution

- + Operates with water pressure - Non electric.
- + Developed for alkaline or acidic additives.
- + Easy to operate. Maintenance without tools.
- + Low pressure loss.
- + Patented technology.

**HIGH
FLOW**



D30 WL

Up to **60 l/h**
of chemical injection



ACS
Informations





Standard equipment : bleeder, suction tube, strainer, connecting flange

Versions : VF or AF seals.

Options : Manual by-pass, external injection.

Features

SPECIFICATIONS	D30WL30000 D30WL30000IE	D30WL5000
Water flow range: (min.-max.):	8 m³/h - 30 m³/h	8 m³/h - 30 m³/h
Operating water temperature:	40° C	40° C
Operating pressure: For external injection model	0.5 - 8 Bar 0.5 - 6 Bar	0.5 - 8 Bar
Injection rate % Ratio	0.003 - 0.03 1:30000 - 1:3000	0.02 - 0.2 1:5000 - 1:500
Chemical injection flow: Min. L/h - Max. L/h US Fl. Oz/min - Min. USGPM - Max	0.24 l/h - 9 l/h 0.135 0.04	1.6 l/h - 60 l/h 0.9 0.26
Connection : CEE USA	Flange DN80 (BSP), or Threads 3» BSP 3» Threads (NPT)	
Hydraulic capacity (Motor Cylinder (2 Clicks) 1.40 Gal US (5.3l)		